ASPEKT System Integration d.o.o.
Požeška br. 67a. Lok. 204, 11030 Beograd, Republika Srbij
Tel. (+ 381 11) 355 7599 Fax. (+ 381 63) 598 033
www.aspekt.rs

CENOVNIK (VP)

25-Sep-25

5780

FOTO	OPIS PROIZVODA / PRODUCT DESCRIPTION	JM	VP CENA (EUR)

ACC. KONTROLERI

1 1 ACAB-001 kom 125.00

ACC. KONTROLER | SERIJA 5780 | TCP/IP | 1 x VRATA | 2 x RFID ČITAČ| 1 x EXIT TASTER
- Q ' ty of users: 20,000 Users; Q ' ty of Event Buffers(offline): 100,000 event buffers
- TCP/IP 10M/100M adaptive, Support APP/4G/Web-server/SDK and Software
- Power Supply: 12VDC 4-7A; Power Consumption of Circuit Board: Less than 100mA
- Size: 160mm x 106mm | -40C~70C; 10-90 % RH, No Condensation
- Garancija: 5 godina

1 2 ACAB-002 kom 145.00

ACC. KONTROLER | SERIJA 5780 | TCP/IP | 2 x VRATA | 4 x RFID ČITAČ| 2 x EXIT TASTER
- Q ' ty of users: 20,000 Users; Q ' ty of Event Buffers(offline): 100,000 event buffers
- TCP/IP 10M/100M adaptive, Support APP/4G/Web-server/SDK and Software
- Power Supply: 12VDC 4-7A; Power Consumption of Circuit Board: Less than 100mA
- Size: 160mm x 106mm | -40C~70C; 10-90 % RH, No Condensation
- Garancija: 5 godina

1 4 ACAB-004 kom 175.00

ACC. KONTROLER | SERIJA 5780 | TCP/IP | 4 x VRATA | 4 x RFID ČITAČ| 4 x EXIT TASTER
- Q ' ty of users: 20,000 Users; Q ' ty of Event Buffers(offline): 100,000 event buffers
- TCP/IP 10M/100M adaptive, Support APP/4G/Web-server/SDK and Software
- Power Supply: 12VDC 4-7A; Power Consumption of Circuit Board: Less than 100mA
- Size: 160mm x 106mm | -40C~70C; 10-90 % RH, No Condensation
- Garancija: 5 godina

1 5 ACAB-TUYA-A01 kom 125.00

ACC. (TUYA) KONTROLER | 5780 | TCP/IP | 2 x Vrata | 2 x RFID Čitač |
- Appearance material PMMA, iron; Working Voltage\Current DC12V+10%\0.5A (no load)
- High-performance 8-bit enhanced MCU; Communication: Wi-Fi/Bluetooth; speed: <0.5s
- User capacity: 1000; authentication mode: Card / password / card+password
- Temporary password: 10; Password support digits: 6-digit password
- Lock outputs 1; Alarm: 1; Exit button: 1; Tamper switch: 1; Magnetic input: 1
- Working environment: -20°C-60°C/10%-90%; IP53; Wall hanging size: 214x166x50mm

1 5 ACAB-TUYA-A01-K kom 195.00

ACC. (TUYA) KONTROLER | 5780 | TCP/IP | 2 x Vrata | 2 x RFID Čitač | KOMPLET
- Appearance material PMMA, iron; Working Voltage\Current DC12V+10%\0.5A (no load)
- High-performance 8-bit enhanced MCU; Communication: Wi-Fi/Bluetooth; speed: <0.5s
- User capacity: 1000; authentication mode: Card / password / card+password
- Temporary password: 10; Password support digits: 6-digit password
- Lock outputs 1; Alarm: 1; Exit button: 1; Tamper switch: 1; Magnetic input: 1
- Working environment: -20°C-60°C/10%-90%; IP53; Wall hanging size: 214x166x50mm

1 7 ACAB-EA05 kom 75.00

ACC. KONTROLIR (Enhanced Alarm Output Controller)
- Work with ACAB-R0 series, ACAB-T01 series, and ACAB-00 series

Zadržavamo pravo promene cena, bez obaveze da vas o tome prethodno obavestimo.
Prikazana slika proizvoda, može, ali i ne mora uvek da odgovara originalu.
Naš moto je: Ništa nije konstatno, osim promene! Heraklit 480pne. © 2004. by www.aspekt.rs

ASPEKT System Integration d.o.o.
Požeška br. 67a. Lok. 204, 11030 Beograd, Republika Srbij
Tel. (+ 381 11) 355 7599 Fax. (+ 381 63) 598 033
www.aspekt.rs

CENOVNIK (VP)

25-Sep-25

5780

FOTO	OPIS PROIZVODA / PRODUCT DESCRIPTION	JM	VP CENA (EUR)

ACC. STAND ALONE KONTROLERI - VRLO ZGODNI ZA PRIMENU

2 7 Sboard-III — kom — 45.00

MINI Double Door Access Controller (Sboard-III); + Remote (Tx Daljinac)
- Za 1xVrata (NO/COM/NC); 1xRFID Čitač; 1xEXIT Taster; WG (In); 12~28VDC
- Indoor; -40°C ~ 60°C; N/Weight 0.1kg; Dimensions L91 x W48 x D20mm
- User Capacity: 999 Users; Adju. Relay Output Time 0~99s
- Multi access modes: Card, Card or PIN, Card with PIN and multi Cards/PINs

2 8 Sboard — kom — 65.00

MINI Single Door Access Controller (Sboard); + Remote (Tx Daljinac)
- Za 1xVrata (NO/COM/NC); 1xRFID Čitač; 1xEXIT Taster; WG (In/Out); 12~24VDC
- Indoor; -40°C ~ 60°C; N/Weight 0.1kg; Dimensions L65 x W54 x D19mm
- User capacity: 1000 Users; Adjustable Relay Output Time 0~99s
- Multi access modes: Card, Card or PIN, Card with PIN and multi Cards/PINs

2 9 Sboard-II — kom — 75.00

MINI Double Door Access Controller (Sboard-II); + Remote (Tx Daljinac)
- Za 1xVrata (NO/COM/NC); 1xRFID Čitač; 2xEXIT Taster; 1xAlarm; WG (In/Out); 12~24VDC
- Indoor; -40°C ~ 60°C; N/Weight 0.1kg; Dimensions L100 x W84 x D26mm
- User capacity: Zone 1 (2000 Users); Zone 2 (100 Users); Adju. Relay Output Time 0~99s
- Multi access modes: Card, Card or PIN, Card with PIN and multi Cards/PINs

2 10 Sboard-BT — kom — 85.00

MINI BLUETOOTH Single Door Access Controller (Sboard-BT); + Remote (Tx Daljinac)
- Za 1xVrata (NO/COM/NC); 1xRFID Čitač; 1xEXIT Taster; WG (In/Out); 12~24VDC
- Indoor; -40°C ~ 60°C; N/Weight 0.1kg; Dimensions L65 x W54 x D19mm
- User Capacity: 1000 Users; Adju. Relay Output Time 0~99s
- Multi access modes: Card, Card or PIN, Card with PIN and multi Cards/PINs

2 11 Sboard-II-WIFI — kom — 95.00

MINI WiFi Double Door Access Controller (Sboard-II-WIFI) APP: WIFI (Android & iOS)
- Za 2xVrata; 1xRFID Čitač; 1xAlarm; 1xDoor Contact; WG (In/Out); 12~24VDC
- Indoor; -40°C ~ 60°C; N/Weight 0.1kg; L100 x W86 x D26(mm)
- User capacity: Zone 1 (2000 Users); Zone 2 (100 Users)
- Multi access modes: Card, Card or PIN, Card with PIN and multi Cards/PINs

2 12 Sboard-II-BT-WIFI — kom — 100.00

MINI WiFi & BLUE TOOTH Access Controller (Sboard-II-BT-WIFI) APP: WIFI (Android & Ios)
- Za 2xVrata; 1xRFID Čitač; 1xAlarm; 1xDoor Contact; WG (In/Out); 12~24VDC
- Indoor; -40°C ~ 60°C; N/Weight 0.1kg; L100 x W86 x D26(mm)
- User capacity: Zone 1 (2000 Users); Zone 2 (100 Users)
- Multi access modes: Card, Card or PIN, Card with PIN and multi Cards/PINs

Zadržavamo pravo promene cena, bez obaveze da vas o tome prethodno obavestimo.
Prikazana slika proizvoda, može, ali i ne mora uvek da odgovara originalu.
Naš moto je: Ništa nije konstatno, osim promene! Heraklit 480pne. © 2004. by www.aspekt.rs

ASPEKT System Integration d.o.o.
Požeška br. 67a. Lok. 204, 11030 Beograd, Republika Srbij
Tel. (+ 381 11) 355 7599 Fax. (+ 381 63) 598 033
www.aspekt.rs

CENOVNIK (VP)

25-Sep-25

5780

FOTO			OPIS PROIZVODA / PRODUCT DESCRIPTION	JM	VP CENA (EUR)
	2	18	Controller-Tuya	kom	125.00

MINI Tuya WiFi Single Door ACC. Controller (Controller-Tuya)
- 1,000 users, user data can be transferred from other Controller
- Multi-access modes: Card, Card or PIN, Card with PIN and multi Cards/PINs
- Can connect with any reader with Wiegand 26~37 bits output
- Can connect with any keypad reader with 4bits, 8bits (ASCII),
- or 10bits Virtual number output
- 1000 APP (Tuya) Users, 500 Common users

ACC. (LIFT) KONTROLERI

	3	1	ACAB-DT10	kom	245.00

ACC. KONTROLER | SERIJA 5780 | TCP/IP | 1 x LIFT | MASTER KONTROLER - ZA 10 SPRATOVA
- Q ' ty of users: 20,000 Users; Q ' ty of Event Buffers(offline): 100,000 event buffers
- TCP/IP 10M/100M adaptive, Support APP/4G/Web-server/SDK and Software
- Power Supply: 12VDC 4-7A; Power Consumption of Circuit Board: Less than 100mA
- Size: 160mm x 106mm | -40C~70C; 10-90 % RH, No Condensation
- Garancija: 5 godina

	3	2	ACAB-DT20	kom	95.00

ACC. KONTROLER | SERIJA 5780 | TCP/IP | 1 x LIFT | MASTER KONTROLER
- Q ' ty of users: 20,000 Users; Q ' ty of Event Buffers(offline): 100,000 event buffers
- TCP/IP 10M/100M adaptive, Support APP/4G/Web-server/SDK and Software
- Power Supply: 12VDC 4-7A; Power Consumption of Circuit Board: Less than 100mA
- Size: 160mm x 106mm | -40C~70C; 10-90 % RH, No Condensation
- Garancija: 5 godina

	3	3	ACAB-DT20K	kom	395.00

ACC. KONTROLER | SERIJA 5780 | TCP/IP | 1 x LIFT | SLAVE KONTROLER - ZA 20 SPRATOVA
- Q ' ty of users: 20,000 Users; Q ' ty of Event Buffers(offline): 100,000 event buffers
- TCP/IP 10M/100M adaptive, Support APP/4G/Web-server/SDK and Software
- Power Supply: 12VDC 4-7A; Power Consumption of Circuit Board: Less than 100mA
- Size: 160mm x 106mm | -40C~70C; 10-90 % RH, No Condensation
- Garancija: 5 godina

RFID ČITAČI KARTICA - WIEGAND PLATFORMA

	4	1	KAR101(EM)	kom	30.00

Serija GB | RFID Citac Kartica | EM 125KHy | Wiegand 26, 34 | rang: 3 ~ 15cm |
- Max. rastojanje od Acc. Kontrol. < 150m | -25°C ~ 70°C | "Water-proof" |LED (red - green)

	4	2	KAR101(MF)	kom	35.00

Serija GB | RFID Citac Kartica | MF: 13.56MHz | Wiegand 34 | rang: 3 ~ 15cm |
- Max. rastojanje od Acc. Kontrol. < 150m | -25°C ~ 70°C | "Water-proof" |LED (red - green)

Zadržavamo pravo promene cena, bez obaveze da vas o tome prethodno obavestimo.
Prikazana slika proizvoda, može, ali i ne mora uvek da odgovara originalu.
Naš moto je: Ništa nije konstatno, osim promene! Heraklit 480pne. © 2004. by www.aspekt.rs

ASPEKT System Integration d.o.o.
Požeška br. 67a. Lok. 204, 11030 Beograd, Republika Srbij
Tel. (+ 381 11) 355 7599 Fax. (+ 381 63) 598 033
www.aspekt.rs

CENOVNIK (VP)

25-Sep-25

5780

FOTO			OPIS PROIZVODA / PRODUCT DESCRIPTION	JM	VP CENA (EUR)
	4	3	KAR600(MF)	kom	30.00
			RFID ČITAČ & TASTATURA | KAR60(MF) | 13.56MHz | WIEGAND | IP65 | 116X75X16mm - Kućište: "ABS+PC with texture"; 6 ~ 12VDC; Max 6 ~ 12mA; 26/34bit Wiegand (default)		
	4	10	UA-P001-EM	kom	30.00
			RFID ČITAČ (UA-P001-EM) | 125KHz | WIEGAND | IP68 | 110x48x20mm - Card type: EM/Mifare; Reading Distance: 3-6 cm - Operating Voltage: 9-12V DC; Quiescent Current: ≤30mA - Operating Temperature: -45°C〜60°C: Operating Humidity: 10%- 90% RH		
	4	11	UA-P001-MF	kom	30.00
			RFID ČITAČ (UA-P001-MF) | 13.56MHz | WIEGAND | IP68 | 110x48x20mm - Card type: EM/Mifare; Reading Distance: 3-6 cm - Operating Voltage: 9-12V DC; Quiescent Current: ≤30mA - Operating Temperature: -45°C〜60°C: Operating Humidity: 10%- 90% RH		
	4	13	UA-P006-MF	kom	30.00
			RFID ČITAČ (UA-P006-MF) | 13.56MHz | WIEGAND | IP68 | 86x86x19mm - Card type: EM/Mifare; Reading Distance: 3-6 cm - Operating Voltage: 9-12V DC; Quiescent Current: ≤30mA - Operating Temperature: -45°C〜60°C: Operating Humidity: 10%- 90% RH		
	4	14	PACD-01	kom	45.00
			RFID ČITAČ (PACD-01) | 13.56MHz & 125KHz | WIEGAND | 86x86x8mm - Card type: EM & Mifare; Reading Distance: 3-6 cm; Material: Acrylic panel - Operating Voltage: 9-12V DC; Quiescent Current: ≤30mA - Operating Temperature: -15°C〜60°C: Operating Humidity: 10%- 90% RH		
	4	15	PACD-101EM	kom	15.00
			RFID ČITAČ (PACD-101) | 125.00KHz | WIEGAND | 122 X 46 X 23mm; Rang 15cm - Napajanje: 4 ~ 14VDC; IP65; Radna temp. -25°C〜65C° - 26bit/34bit Wiegand (default)		
	4	16	PACD-101MF	kom	17.00
			RFID ČITAČ (PACD-101) | 13.56MHz | WIEGAND | 122 X 46 X 23mm; Rang 8cm - Napajanje: 4 ~ 14VDC; IP65; Radna temp. -25°C〜65C° - 26bit/34bit Wiegand (default)		

Zadržavamo pravo promene cena, bez obaveze da vas o tome prethodno obavestimo.
Prikazana slika proizvoda, može, ali i ne mora uvek da odgovara originalu.
Naš moto je: Ništa nije konstatno, osim promene! Heraklit 480pne. © 2004. by www.aspekt.rs

ASPEKT System Integration d.o.o.
Požeška br. 67a. Lok. 204, 11030 Beograd, Republika Srbij
Tel. (+ 381 11) 355 7599 Fax. (+ 381 63) 598 033
www.aspekt.rs

CENOVNIK (VP)

25-Sep-25

5780

FOTO	OPIS PROIZVODA / PRODUCT DESCRIPTION	JM	VP CENA (EUR)
	4 17 PACD-102 RFID ČITAČ (PACD-102 | 13.56MHz, ili 125KHz | WIEGAND | 124 x 76x 23.5mm	kom	30.00
	4 18 aButton(MF) RFID ČITAČ (aButton) | 13.56MHz| WIEGAND | Dimensions: Ø25mm/Ø20mm x 22mm	kom	25.00
	4 19 aButton(EM) RFID ČITAČ (aButton) | 125.00KHz | WIEGAND | Dimensions: Ø25mm/Ø20mm x 22mm	kom	25.00
	4 20 Ø20-25-EM RFID ČITAČ (Ø20-25-EM) | 125.00KHz | WIEGAND | Dimensions: Ø25mm/Ø20mm x 22mm	kom	20.00
	4 21 Ø20-25-MF RFID ČITAČ (Ø20-25-MF) | 13.56MHz | WIEGAND | Dimensions: Ø25mm/Ø20mm x 22mm	kom	20.00
	4 23 PACD-103EM RFID ČITAČ (PACD) | 125KHz | WIEGAND | IP65 | 109 X 88.4 X34mm | ABS - Card type: EM/Mifare; Reading Distance: 3-6 cm - Operating Voltage: 6-14V DC; Quiescent Current: ≤30mA - Operating Temperature: -25°C∼60°C: Operating Humidity: 10%- 90% RH	kom	40.00
	4 24 PACD-103MF RFID ČITAČ (PACD) | 13.56MHz | WIEGAND | IP65 | 109 X 88.4 X34mm | ABS - Card type: EM/Mifare; Reading Distance: 3-6 cm - Operating Voltage: 6-14V DC; Quiescent Current: ≤30mA - Operating Temperature: -25°C∼60°C: Operating Humidity: 10%- 90% RH	kom	45.00

Zadržavamo pravo promene cena, bez obaveze da vas o tome prethodno obavestimo.
Prikazana slika proizvoda, može, ali i ne mora uvek da odgovara originalu.
Naš moto je: Ništa nije konstatno, osim promene! Heraklit 480pne. © 2004. by www.aspekt.rs

ASPEKT System Integration d.o.o.
Požeška br. 67a. Lok. 204, 11030 Beograd, Republika Srbij
Tel. (+ 381 11) 355 7599 Fax. (+ 381 63) 598 033
www.aspekt.rs

CENOVNIK (VP)

25-Sep-25

5780

FOTO	OPIS PROIZVODA / PRODUCT DESCRIPTION	JM	VP CENA (EUR)
	4 25 RAF006EM	kom	40.00
	RFID ČITAČ (RAF006EM) | 125KHz | WIEGAND | IP65 |120X56X18mm | ABS+PC with texture - Card type: EM/Mifare; Reading Distance: 3-6 cm| Anti-vandal - Operating Voltage: 6-14V DC; Quiescent Current: ≤30mA - Operating Temperature: -25°C〜60°C: Operating Humidity: 10%- 90% RH		
	4 26 RAF006MF	kom	45.00
	RFID ČITAČ (RAF006MF) | 13.56MHz | WIEGAND | IP65 | 120X56X18mm |ABS+PC with texture - Card type: EM/Mifare; Reading Distance: 3-6 cm| Anti-vandal - Operating Voltage: 6-14V DC; Quiescent Current: ≤30mA - Operating Temperature: -25°C〜60°C: Operating Humidity: 10%- 90% RH		
	4 27 SA6-RX	kom	55.00
	RFID ČITAČ (RAF006MF) | EM/H/MF | WIEGAND | IP66 | 47*30*19mm |METAL - Card type: EMHID//Mifare; Reading Distance: ~10cm | Anti-vandal - Operating Voltage: 9-24V DC; Quiescent Current: ≤30mA - Operating Temperature: -40°C〜60°C: Operating Humidity: 10%- 90% RH		
	4 31 CAC3	kom	70.00
	CAC3 - RFID (125KHz) ČITAČ KARTICA SA TASTATUROM | WG I SAMOSTALAN| IP68 - Card type: EM, HID, MF, CPU Card; (Factory default: EM 125KHz) - Card users 2,000; CODE Users2,000; Relay NO/NC/COM output - Standalone for single door, Standalone for two doors - With external reader for two doors | Two units interlocked for two doors - Anti-passback for single door; Anti-passback for two doors		
	4 32 KAR602EM	kom	30.00
	RFID ČITAČ & TASTATURA | KAR602Mifare | 125.00KHz | WIEGAND | IP65 |86x86x20mm - Kućište: "Aluminum alloy"; Tastatura " ne uništiva" | DC 6 ~ 12VDC; Max 6 ~ 12mA		
	4 33 KAR602Mifare	kom	45.00
	RFID ČITAČ & TASTATURA | KAR602Mifare | 13.56MHz | WIEGAND | IP65 |86x86x20mm - Kućište: "Aluminum alloy"; Tastatura " ne uništiva" | DC 6 ~ 12VDC; Max 6 ~ 12mA		
	4 34 ART8(EM)	kom	50.00
	RFID touch-screen Reader with pincode - EM 125.00KHz - Metal & IP68 Waterproof Pincode Card Reader; EM/Mifare; 9-16V DC, DC12V; ≤30mA - Conforms to IP68; 3-6 cm; -45〜60℃, 10%〜90%, WG26/34, 86*86*20mm, 0.4KG - 54PCS; 22.6KG, 56*40*41cm		

Zadržavamo pravo promene cena, bez obaveze da vas o tome prethodno obavestimo.
Prikazana slika proizvoda, može, ali i ne mora uvek da odgovara originalu.
Naš moto je: Ništa nije konstatno, osim promene! Heraklit 480pne. © 2004. by www.aspekt.rs

ASPEKT System Integration d.o.o.
Požeška br. 67a. Lok. 204, 11030 Beograd, Republika Srbij
Tel. (+ 381 11) 355 7599 Fax. (+ 381 63) 598 033
www.aspekt.rs

CENOVNIK (VP)

25-Sep-25

5780

FOTO	OPIS PROIZVODA / PRODUCT DESCRIPTION	JM	VP CENA (EUR)
	4 35 ART8(MF)	kom	55.00

RFID touch-screen Reader with pincode - MF 15.56MHz
- Metal & IP68 Waterproof Pincode Card Reader; EM/Mifare; 9-16V DC, DC12V; ≤30mA
- Conforms to IP68; 3-6 cm; -45～60℃, 10%～90%, WG26/34, 86*86*20mm, 0.4KG
- 54PCS; 22.6KG, 56*40*41cm

	4 37 A4A-QR701-EM	kom	95.00

QR Code and Card Reader (A4A-QR701-EM): EM (125.00KHz)
- Voltage: DC12V; Current <60mA; Temperature-40°-+85°; 10%~90% RH(non-condensing)
- Size 120*72*18mm; Read card type EM、Mifare、15693、desfire(Options)
- Scan type Bar code、QR code; Interface type: Wiegand、RS232、RS485、TTL
- Material: Tempered glass+Metal; Waterproof IP68; Night lamp: Yes

	4 38 A4A-QR701-MF	kom	100.00

QR Code and Card Reader (A4A-QR701-MF): MF (13.56MHz)
- Voltage: DC12V; C current <60mA; Temperature-40°-+85°; 10%~90% RH(non-condensing)
- Size 120*72*18mm; Read card type EM、Mifare、15693、desfire(Options)
- Scan type Bar code、QR code; Interface type: Wiegand、RS232、RS485、TTL
- Material: Tempered glass+Metal; Waterproof IP68; Night lamp: Yes

	4 40 PACD-100A-EM	kom	40.00

RFID ČITAČ & TASTATURA | PACD-100A-EM | 125.00KHz | RS485 & WG | Vodo-otporan
- Kućište PVC; 5 ~ 16VDC Max 25mA; -30°C～85C°; Opseg čitanja 15cm

	4 41 PACD-100A-MF	kom	45.00

RFID ČITAČ & TASTATURA | PACD-100A-MF | 13.56MHz | RS485 & WG | Vodo-otporan
- Kućište PVC; 5 ~ 16VDC Max 25mA; -30°C～85C°; Opseg čitanja 8cm

	4 45 RFID-MIDDLE-125	kom	145.00

RFID ČITAČ SREDNJEG DOMETA (<120cm); 125KHz; WG OUT; Spoljna primena
- Middle Reading Distance Range (Up to 40") Wiegand 26-bit
- 125KHz RFID Proximity Card Reader for Access Control Parking System

BLUE TOOTH & RFID ČITAČ NA WIEGAND PLATFORMI

	5 1 BTOOTH-86MF	kom	45.00

BLUE TOOTH ČITAČ | 13.56 MHz; Mobile Blue tooth 4.0 | WG 26/34
- Working voltage: DC 9-12V; Support Bluetooth 4.0 on Android 4.4 or IOS 7.0
- Reading distance: RFID Card: 1 ~ 5cm; bluetooth: 0 ~ 5m
- Operating Temperature: 20°C～65°C: Operating Humidity: 0%- 95%

Zadržavamo pravo promene cena, bez obaveze da vas o tome prethodno obavestimo.
Prikazana slika proizvoda, može, ali i ne mora uvek da odgovara originalu.
Naš moto je: Ništa nije konstatno, osim promene! Heraklit 480pne. © 2004. by www.aspekt.rs

ASPEKT System Integration d.o.o.
Požeška br. 67a. Lok. 204, 11030 Beograd, Republika Srbij
Tel. (+ 381 11) 355 7599 Fax. (+ 381 63) 598 033
www.aspekt.rs

CENOVNIK (VP)

25-Sep-25

5780

FOTO	OPIS PROIZVODA / PRODUCT DESCRIPTION	JM	VP CENA (EUR)

BIOMETRIJSKA OPREMA, TCP/IP, WIEGAND PLATFORMI, ALI I SAMOSTALNI

6 1 FA-601 — kom — 80.00

FA-601 - SKENER OTISKA PRSTA & RFID (125KHz) | SAMOSTALAN & WG PLATFORMA |
- Card type: EM, HID, MF, CPU Card; (Factory default: EM 125KHz); Option MF 13.56MHz
- Operate by infrared remote; > 10,000 card users and 300 fingerprint users
- Relay NO/NC/COM output

6 2 FA-602 — kom — 85.00

FA-602 - SKENER OTISKA PRSTA & RFID (125KHz) | SAMOSTALAN & WG PLATFORMA |
- Card type: EM, HID, MF, CPU Card; (Factory default: EM 125KHz)
- Operate by infrared remote; > 10,000 card users and 300 fingerprint users
- Relay NO/NC/COM output

6 3 FAR-002 — kom — 175.00

SKENER OTISKA PRSTA | TCP/IP & WG PLATFORMA | ZA PRST I RFID (MF) KARTICU
- Input Voltage: 12VDC; Static current: ≤150mA; Working current: ≤300mA
- Fingerprint capacity: 1000; Fingerprint resolution: 450DPI
- Fingerprint research time: <1.0S
- Fingerprint recognition false rate: <0.001%; False Reject Rate: <1.0%
- Working temperature: -20°C ~ 50°C; Working humidity: 20% ~ 95%
- Metal case; Dimension: 179 * 89 * 45mm

6 4 FAR-002S — kom — 175.00

SKENER OTISKA PRSTA | USB | ZA LAKO IZDAVANJE AUTORIZACIJA OTISCIMA PRSTIJU
- FAR-002S USB Fingerprint reader issuing device to work with FR-002 reader only
- Easy to authorize users by finger or Mifare 13.56MHz cards

6 5 TAF1-EM — kom — 95.00

OTISAK PRSTA & RFID ČITAČ & TASTATURA | TAF1-EM 125KHz | STANDALONE | WG IN
- Fingerprint users 500; Card Users 10,000; Option IC (13.56MHz)
- Operating Temperature: -45°C~60°C: Operating Humidity: 10%- 90% RH
- Metal structure | Dimensions: 139x70x22mm; Weight: 350g
- Card type options: EM, HID, MF, CPU Card (Difault: EM 125.00KHz)

6 7 TAF1-MF — kom — 115.00

OTISAK PRSTA & RFID ČITAČ & TASTATURA | TAF1-MF; 13.56MHz | STANDALONE | WG IN
- Fingerprint users 500; Card Users 10,000; Option IC (13.56MHz)
- Operating Temperature: -45°C~60°C: Operating Humidity: 10%- 90% RH
- Metal structure | Dimensions: 139x70x22mm; Weight: 350g
- Card type options: EM, HID, MF, CPU Card (Difault: EM 125.00KHz)

Zadržavamo pravo promene cena, bez obaveze da vas o tome prethodno obavestimo.
Prikazana slika proizvoda, može, ali i ne mora uvek da odgovara originalu.
Naš moto je: Ništa nije konstatno, osim promene! Heraklit 480pne. © 2004. by www.aspekt.rs

ASPEKT System Integration d.o.o.
Požeška br. 67a. Lok. 204, 11030 Beograd, Republika Srbij
Tel. (+ 381 11) 355 7599 Fax. (+ 381 63) 598 033
www.aspekt.rs

CENOVNIK (VP)

25-Sep-25

5780

FOTO	OPIS PROIZVODA / PRODUCT DESCRIPTION	JM	VP CENA (EUR)
	6 8 SA300A	kom	135.00
	OTISAK PRSTA & RFID ČITAČ & TASTATURA & APP (Tuya) SA300A | STANDALONE | WG OUT - Fingerprint users 300; Card 1,000; Code 1,000; Operating Temperature -40℃〜60℃		
	6 9 JA300X	kom	145.00
	OTISAK PRSTA & RFID ČITAČ & TASTATURA & APP (Tuya) JA300X | STANDALONE | WG OUT - Fingerprint users 300; Card 1,000; Code 1000; Operating Temperature -20℃〜50℃		
	6 10 TAF1-WIFI	kom	175.00
	OTISAK PRSTA & RFID ČITAČ & TASTATURA & APP (Tuya) TAF1-WIFI | STANDALONE | WG OUT - Fingerprint users 600; Card Users 10,000; Operating Temperature: -45°C〜60°; IP6 - Operating Voltage: DC 12-24V; Standby Current: ≤35mA; Operation Current ≤100mA - Metal backlight keypad; Dimensions: 139 x 70 x 20mm - Card type options: EM, HID, MF, CPU Card (Difault: EM 125.00KHz)		
	6 11 KA2-BT-M1	kom	95.00
	RFID ČITAČ - TASTATURA (KA2-BT-M1) | WiFi & BLUETOOTH | 13.56MHz - MIFARE Card capacity - 20,000; Unlock time: 1.5s; APP - TTLock (Za mob. telefon) Power supply: 12VDC; Stand-by current: 5mA; Operating current: 1A Material - Aluminum alloy frame, Glass panel; Colour: Gray; 125x79x15.5mm		
	6 12 KA5	kom	145.00
	DATA TERMINAL | KA5 | Prepoznavanje geometrije lica; RFID Kartice, Šifre; APP TTLock - RFID Kartica (1000); Prepoznavanje geometrije lica (100)		
	6 13 KA5F	kom	195.00
	DATA TERMINAL | KA5F | Prepoznavanje geom. lica; Otisak; RFID Kartica, Šifra; APP TTLock - RFID Kartica (1000); Prepoznavanje geometrije lica (100); skeniranje otiska prsta (100)		
	6 15 IPCCTV-A200	kom	295.00
	KAMERA (CCATV-200) ZA PREPOZNAVANJE GEOMETRIJE LICA - 12VDC; 2.0 M pixels; 25fps - Profesionalni sistem evidencije i kontrole pristupa - CCTV Integrated Camera with Access control function, - Support Web-server to authorize new users and monitor it at real-time - Dimension: 197x95x82mm; Embedded LINUX Operating System - Upload method: FTP, SDK call upload		

Zadržavamo pravo promene cena, bez obaveze da vas o tome prethodno obavestimo.
Prikazana slika proizvoda, može, ali i ne mora uvek da odgovara originalu.
Naš moto je: Ništa nije konstatno, osim promene! Heraklit 480pne. © 2004. by www.aspekt.rs

ASPEKT System Integration d.o.o.
Požeška br. 67a. Lok. 204, 11030 Beograd, Republika Srbij
Tel. (+ 381 11) 355 7599 Fax. (+ 381 63) 598 033
www.aspekt.rs

CENOVNIK (VP)

25-Sep-25

5780

FOTO	OPIS PROIZVODA / PRODUCT DESCRIPTION	JM	VP CENA (EUR)
	7 19 TA-5MF RFID ČITAČ & TASTATURA (TA-5MF) | 13.56MHz | STANDALONE & WG IN/OUT Metal case, anti-vandal; Digital backlit touch keypad; WG interface: WG26 Input / output Capacity: 2000 cards / codes; Three accesses: card, pin, card + pin	kom	55.00
	7 20 T1A2-EM RFID ČITAČ - TOUCH TASTATURA (TA12-EM) | 125KHz | STANDALONE & WG OUT	kom	30.00
	7 21 TA12-M1 RFID ČITAČ - TOUCH TASTATURA (TA12-M1) | 13.56MHz | STANDALONE & WG OUT	kom	30.00
	7 22 TA12 WiFi-MF RFID ČITAČ | TA12 WiFi | MF | STANDALONE & WiFi & WG OUT | APP: Tuya - DC12-24V | -40C°~60° | WiFi Touch Screen Standalone Access Controller; EM or MF - User Capacity: 2000 Cards; Reading Distance: 3-6 cm; Size: 117x71x22mm	kom	55.00
	7 25 ASA-TS2IB-EM RFID ČITAČ (ASA-TS21B-EM) | 125KHz | STANDALONE & WG IN/OUT | IP65 - Reading Distance: 1-15 cm; Operating Voltage: 12V DC; Quiescent Current: ≤100mA - Operating Temperature: -45°C~60°C: Operating Humidity: 10%- 90% RH - USERS: 15000 | Aluminum alloy | Dimensions: 125×84×23mm; Weight: 350g	kom	35.00
	7 26 ASA-TS2IB-MF RFID ČITAČ (ASA-TS21B-MF | 13.56MHz | STANDALONE & WG IN/OUT | IP65 - Reading Distance: 1-15 cm; Operating Voltage: 12V DC; Quiescent Current: ≤100mA - Operating Temperature: -45°C~60°C: Operating Humidity: 10%- 90% RH - USERS: 15000 | Aluminum alloy | Dimensions: 125×84×23mm; Weight: 350g	kom	40.00
	7 27 ASA-TS2I-EM RFID ČITAČ & TASTATURA (ASA-TS21-EM) | 125.00KHz | STANDALONE & WG IN/OUT ◆Metal case, anti-vandal; Digital backlit touch keypad; IP65; 125*85*23mm ◆controller and reader; WG26 output/Input; Capacity: 2000 cards / codes ◆Three way to open the door: card, password, card + password	kom	50.00

Zadržavamo pravo promene cena, bez obaveze da vas o tome prethodno obavestimo.
Prikazana slika proizvoda, može, ali i ne mora uvek da odgovara originalu.
Naš moto je: Ništa nije konstatno, osim promene! Heraklit 480pne. © 2004. by www.aspekt.rs

ASPEKT System Integration d.o.o.
Požeška br. 67a. Lok. 204, 11030 Beograd, Republika Srbij
Tel. (+ 381 11) 355 7599 Fax. (+ 381 63) 598 033
www.aspekt.rs

CENOVNIK (VP)

25-Sep-25

5780

FOTO	OPIS PROIZVODA / PRODUCT DESCRIPTION	JM	VP CENA (EUR)
	7 28 ASA-TS2I-MF RFID ČITAČ & TASTATURA (ASA-TS21-MF) | 13.56MHz | STANDALONE & WG IN/OUT ◆Metal case, anti-vandal; Digital backlit touch keypad; IP65; 125*85*23mm ◆controller and reader; WG26 output/Input; Capacity: 2000 cards / codes ◆Three way to open the door: card, password, card + password	kom	55.00
	7 35 S600-EM RFID ČITAČ & TASTATURA (SA600-EM) | 125KHz | STANDALONE & ANTI-VANDAL | WG OUT - Reading Distance: 1-8 cm; Operating Voltage: 12V DC; Quiescent Current: ≤35mA - Operating Temperature: -45°C~60°C: Operating Humidity: 10%- 90% RH - USERS: 2000 |Metal structure | Dimensions: 120*56*20mm; Weight: 350g	kom	55.00
	7 36 SA600-MF RFID ČITAČ & TASTATURA (SA600-FM) | 13.56MHz | STANDALONE & ANTI-VANDAL | WG OUT - Reading Distance: 1-8 cm; Operating Voltage: 12V DC; Quiescent Current: ≤35mA - Operating Temperature: -45°C~60°C: Operating Humidity: 10%- 90% RH - USERS: 2000 |Metal structure | Dimensions: 120*56*20mm; Weight: 350g	kom	60.00
	7 37 S601-W-EM RFID ČITAČ & TASTATURA (SA601-W-EM) | 125KHz | STANDALONE | WG IN - METALNO KUĆIŠTE; SILICON KEYPAD | ANTI-VANDAL | IP68 - Reading Distance: 1-8 cm; Operating Voltage: 12V DC; Quiescent Current: ≤35mA - Operating Temperature: -45°C~60°C: Operating Humidity: 10%- 90% RH - USERS: 2000 |Metal structure | Dimensions: 120*56*20mm; Weight: 350g	kom	55.00
	7 38 S601-W-FM RFID ČITAČ & TASTATURA (SA601-FM) | 13.56MHz | STANDALONE | WG OUT - METALNO KUĆIŠTE; SILICON KEYPAD | ANTI-VANDAL | IP68 - Reading Distance: 1-8 cm; Operating Voltage: 12V DC; Quiescent Current: ≤35mA - Operating Temperature: -45°C~60°C: Operating Humidity: 10%- 90% RH - USERS: 2000 |Metal structure | Dimensions: 120*56*20mm; Weight: 350g	kom	60.00
	7 40 SAA-TS22-MF RFID ČITAČ SA TOUCH TASTATUROM (SAA-TS22-MF) | 13.56MHz | STANDALONE & WG IN	kom	30.00
	7 41 CA800-B RFID ČITAČ & TASTATURA & LCD (CA800-B) | 13.56MHz | STANDALONE-USB & WG IN - Korisnika <1000 (ID Kartica / Šifara; Pamti 100,000 Rekoda do statusa "memory full" - Rekordi se "skidaju" na USB Disk u formatu .xls; .txt; Dimenzije: 117 x 78 x 22mm - Idealan i kao sistem Evidencije i kontrole pristupa za manja preduzeća	kom	75.00

RFID ČITAČI KARTICA - BEŽIČNI - WIEGAND PLATFOMA

Zadržavamo pravo promene cena, bez obaveze da vas o tome prethodno obavestimo.
Prikazana slika proizvoda, može, ali i ne mora uvek da odgovara originalu.
Naš moto je: Ništa nije konstatno, osim promene! Heraklit 480pne. © 2004. by www.aspekt.rs

ASPEKT System Integration d.o.o.
Požeška br. 67a. Lok. 204, 11030 Beograd, Republika Srbij
Tel. (+ 381 11) 355 7599 Fax. (+ 381 63) 598 033
www.aspekt.rs

CENOVNIK (VP)

25-Sep-25

5780

FOTO	OPIS PROIZVODA / PRODUCT DESCRIPTION	JM	VP CENA (EUR)
	8 1 WAR1-B RFID ČITAČ (WAR1-MF-B) | BEŽIČNI | 13.56MHz - MIFARE | WIEGAND | BOJA: CRNA - 433MHz Rolling Code technology; Isporučuje se bez baterija (ide 3 x AAA) - RFID Čirač L134 x W55 x H20 (mm); -20°C〜60°C - Receiver L25 x W50 (mm); 30g | Communication Distance 30m Maximum	kom	45.00
	8 2 WAR1-W RFID ČITAČ (WAR1-MF-W) | BEŽIČNI | 13.56MHz - MIFARE | WIEGAND | BOJA: BELA - 433MHz Rolling Code technology; Isporučuje se bez baterija (ide 3 x AAA) - RFID Čirač L134 x W55 x H20 (mm); -20°C〜60°C - Receiver L25 x W50 (mm); 30g | Communication Distance 30m Maximum	kom	45.00
	8 3 WAK1-EM RFID ČITAČ - TASTATURA (WAK1-EM) | BEŽIČNI | 125KHz - EM | WIEGAND - 433MHz Rolling Code technology; Isporučuje se bez baterija (ide 3 x AAA) - RFID Čirač L134 x W55 x H20 (mm); -20°C〜60°C - Receiver L25 x W50 (mm); 30g | Communication Distance 30m Maximum	kom	50.00
	8 4 WAK1-MF RFID ČITAČ - TASTATURA (WAK1-MF) | BEŽIČNI | 13.56MHz - MIFARE | WIEGAND - 433MHz Rolling Code technology; Isporučuje se bez baterija (ide 3 x AAA) - RFID Čirač L134 x W55 x H20 (mm); -20°C〜60°C - Receiver L25 x W50 (mm); 30g | Communication Distance 30m Maximum	kom	55.00
	8 5 ACAM28A RFID ČITAČ - TASTATURA | BEŽIČNI |125KHz & 13.56MHz & HID | WIEGAND - 433MHz Rolling Code technology; Isporučuje se bez baterija (ide 3 x AAA) - RFID Čirač L134 x W55 x H20 (mm); -20°C〜60°C - Receiver L25 x W50 (mm); 30g | Communication Distance 30m Maximum	kom	70.00

RFID ČITAČI SA TATSTATUROM | STANDALONE & WiFi & WG OUT

	9 1 KA35 WiFi RFID ČITAČ - SAMOSTALAN | BEŽIČNI | (KA35 WiFi) | 12~24VDC | MF1 | WG In/OUT - Mobile APP, RFID Card, CODE, RFID Card + CODE	kom	55.00
	9 2 SAK7 RFID ČITAČ - TASTATURA (SAK7) | EM 125.00KHz | BEŽIČNI (433MHz, Rolling Code) - Isporučuje se bez baterija (Potrebne 3 x AAA) i sa 1 x Remote (Tx) - Autorizacija: RFID Card (Tag), CODE, Remote (Tx)	kom	70.00

Zadržavamo pravo promene cena, bez obaveze da vas o tome prethodno obavestimo.
Prikazana slika proizvoda, može, ali i ne mora uvek da odgovara originalu.
Naš moto je: Ništa nije konstatno, osim promene! Heraklit 480pne. © 2004. by www.aspekt.rs

ASPEKT System Integration d.o.o.
Požeška br. 67a. Lok. 204, 11030 Beograd, Republika Srbij
Tel. (+ 381 11) 355 7599 Fax. (+ 381 63) 598 033
www.aspekt.rs

CENOVNIK (VP)

25-Sep-25

5780

FOTO	OPIS PROIZVODA / PRODUCT DESCRIPTION	JM	VP CENA (EUR)

BARCODE (QR) SKENERI I SA INTEGRISANIM RFID ČITAČEM KARTICA

10 1 | AE20-WIEGAND-PL | kom | 115.00

BARCODE SKENER (FIKSNI; CMOS) | QR, 2D, 1D | USB & WIEGAND (WG)
- Dimenzije: 50.5mm×50mm×25mm | -20℃~55℃; Konekcija: wiegand 26 + usb

10 2 | QRS-86EM-WG | kom | 120.00

BARCODE SKENER (1D, 2D, QR) & RFID ČITAČ KARTICA (EM: 125KHz) | WIEGAND
- Dimension: 86L X 86W X42H (mm) | Material: PC and Tempered glass
- Voltage: 4-15V input | working current: 800mA | -25C°~65°C
- Reading direction: 45°; reading speed: ＜200ms; reading distance: 0-20cm
- Read 1D Code Type: EAN, UPC, Code 39, Code 93, Code 128, UCC/EAN 128, Codabar Interleaved 2 of 5, Standard 25, MSI-Plessey, GS1 Databar, Industrial 25, Matrix 2 of 5
- Port: Wiegand, RS485, RS232, USB, TCP/IP (kod poručivanja naznačiti željeni)

10 3 | QRS-86MF-WG-USB | kom | 125.00

BARCODE SKENER (1D, 2D, QR) & RFID ČITAČ KARTICA (MF: 13.56MHz) | WG & USB
- Dimension: 86L X 86W X42H (mm) | Material: PC and Tempered glass
- Voltage: 4-15V input | working current: 800mA | -25C°~65°C
- Reading direction: 45°; reading speed: ＜200ms; reading distance: 0-20cm
- Read 1D Code Type: EAN, UPC, Code 39, Code 93, Code 128, UCC/EAN 128, Codaba Interleaved 2 of 5, Standard 25, MSI-Plessey, GS1 Databar, Industrial 25, Matrix 2 of 5
- Port: Wiegand, RS485, RS232, USB, TCP/IP (kod poručivanja naznačiti željeni)

10 4 | QRS-86EM | kom | 135.00

BARCODE SKENER (1D, 2D, QR) & RFID ČITAČ KARTICA (EM: 125.00MHz) | TCP/IP
- Dimension: 86L X 86W X42H (mm) | Material: PC and Tempered glass
- Voltage: 4-15V input | working current: 800mA | -25C°~65°C
- Reading direction: 45°; reading speed: ＜200ms; reading distance: 0-20cm
- Read 1D Code Type: EAN, UPC, Code 39, Code 93, Code 128, UCC/EAN 128, Codaba Interleaved 2 of 5, Standard 25, MSI-Plessey, GS1 Databar, Industrial 25, Matrix 2 of 5
- Port: Wiegand, RS485, RS232, USB, TCP/IP (kod poručivanja naznačiti željeni)

10 5 | QRS-86MF | kom | 145.00

BARCODE SKENER (1D, 2D, QR) & RFID ČITAČ KARTICA (MF: 13.56MHz) | TCP/IP
- Dimension: 86L X 86W X42H (mm) | Material: PC and Tempered glass
- Voltage: 4-15V input | working current: 800mA | -25C°~65°C
- Reading direction: 45°; reading speed: ＜200ms; reading distance: 0-20cm
- Read 1D Code Type: EAN, UPC, Code 39, Code 93, Code 128, UCC/EAN 128, Codaba Interleaved 2 of 5, Standard 25, MSI-Plessey, GS1 Databar, Industrial 25, Matrix 2 of 5
- Port: Wiegand, RS485, RS232, USB, TCP/IP (kod poručivanja naznačiti željeni)

RFID (UHF) ČITAČI KARTICA - WIEGAND PLATFORMA I RFID (UHF) NOSIOCI IDENTIFIKACIJE

Zadržavamo pravo promene cena, bez obaveze da vas o tome prethodno obavestimo.
Prikazana slika proizvoda, može, ali i ne mora uvek da odgovara originalu.
Naš moto je: Ništa nije konstatno, osim promene! Heraklit 480pne. © 2004. by www.aspekt.rs

ASPEKT System Integration d.o.o.
Požeška br. 67a. Lok. 204, 11030 Beograd, Republika Srbij
Tel. (+ 381 11) 355 7599 Fax. (+ 381 63) 598 033
www.aspekt.rs

CENOVNIK (VP)

25-Sep-25

5780

FOTO	OPIS PROIZVODA / PRODUCT DESCRIPTION	JM	VP CENA (EUR)
	11 1 UHF-A05 RFID ČITAČ | UHF-A05 | DESK TOP: do 200mm | UHF 865~868MHz - Protocol: ISO18000-6B,ISO18000-6C (EPC GEN2) | Komunikacija: USB - Operating Voltage: DC12V 80MA | Size: 121x78x22mm | Weight: 0.1kg - Free DLL and DEMO Software source code to facilitate further development	kom	85.00
	11 2 UHF-A001 RFID ČITAČ | UHF-A001 | OPSEG ČITANJA: 0 ~ 3m | UHF 865~868MHz - Protocol: ISO18000-6B,ISO18000-6C (EPC GEN2) | Komunikacija: WG26, WG34, RS485 - Operating Voltage: DC12V 80MA | Size: 121x78x22mm | Weight: 0.5kg	kom	125.00
	11 3 UHF-A202406 RFID ČITAČ |UHF-A202406 | opseg: 0 ~ 6m | UHF 865~868MHz | IP67 | Antena integrisana - Protocol: ISO18000-6B,ISO18000-6C (EPC GEN2) | Komunikacija: WG (24, 36), RS485 - Operating Voltage: 12VDC | Dimenzije: 180x180x60mm/265x185x70mm - Radna Temperatura -20°C~+70°C | Opciono, komunikacija: TCP/IP, WIFI, GPRS, etc.	kom	245.00
	11 4 UHF-A202415 RFID ČITAČ |UHF-A202415 | opseg: 0 ~ 15m | UHF 865~868MHz | IP67 | Antena integrisana - Protocol: ISO18000-6B,ISO18000-6C (EPC GEN2) | Komunikacija: WG (24, 36), RS485 - Operating Voltage: 12VDC | Dimenzije: 180x180x60mm/ 265x185x70mm - Radna Temperatura -20°C~+70°C | Opciono, komunikacija: TCP/IP, WIFI, GPRS, etc.	kom	275.00
	11 5 UHF-A202420 RFID ČITAČ |UHF-A202420 | opseg: 0 ~ 20m | UHF 865~868MHz | IP67 | Antena integrisana - Protocol: ISO18000-6B,ISO18000-6C (EPC GEN2) | Komunikacija: WG (24, 36), RS485 - Operating Voltage: 12VDC | Dimenzije: 260*260*70mm/ 355*260*80mm - Radna Temperatura -20°C~+70°C | Opciono, komunikacija: TCP/IP, WIFI, GPRS, etc.	kom	295.00
	11 7 UHF-A105 RFID ČITAČ | UHF-A105 | OPSEG ČITANJA: 0 ~ 5m | UHF 865~868MHz | IP67 | Antena 8dbi - Protocol: ISO18000-6B,ISO18000-6C (EPC GEN2) | Komunikacija: WG26, WG34, RS485 - Operating Voltage: DC12V 80MA | Size: 121x78x22mm | Weight: 0.5kg	kom	195.00
	11 8 UHF-A115 RFID ČITAČ | UHF-A115 | OPSEG ČITANJA: 5 ~ 15 (50)m | UHF 865~868MHz | IP67 | - Protocol: ISO18000-6B,ISO18000-6C (EPC GEN2) | Komunikacija: WG26, WG34, RS485 - Operating Voltage: DC12V 80MA | Size: 121x78x22mm | Weight: 0.5kg	kom	295.00

RFID (UHF) KARTICE, NALEPNICE, TAG-OVI ITD.

Zadržavamo pravo promene cena, bez obaveze da vas o tome prethodno obavestimo.
Prikazana slika proizvoda, može, ali i ne mora uvek da odgovara originalu.
Naš moto je: Ništa nije konstatno, osim promene! Heraklit 480pne. © 2004. by www.aspekt.rs

ASPEKT System Integration d.o.o.
Požeška br. 67a. Lok. 204, 11030 Beograd, Republika Srbij
Tel. (+ 381 11) 355 7599 Fax. (+ 381 63) 598 033
www.aspekt.rs

CENOVNIK (VP)

25-Sep-25

5780

FOTO	OPIS PROIZVODA / PRODUCT DESCRIPTION	JM	VP CENA (EUR)
	12 10 ID&IC CARD RFID PASSIVE ID CARD | Frequency: 125KHz & 13.56MHz - Protocol: ISO/ICE18000-6C EPS Gen 2 | Size: 85.5x54mm	kom	0.95
	12 11 A9962 UHF RFID PASSIVE LONG RANGE ID CARD | Frequency: 860~960MHz - Protocol: ISO/ICE18000-6C EPS Gen 2 | Size: 85.5x54mm	kom	1.00
	12 12 A9962+ID UHF RFID PASSIVE LONG RANGE ID CARD | Frequency: 860~960MHz & EM (125KHz) - Protocol: ISO/ICE18000-6C EPS Gen 2 | Size: 85.5x54mm - Protocol: ISO/18000-6C +14443A	kom	1.45
	12 13 A9962+IC UHF RFID PASSIVE LONG RANGE ID CARD | Frequency: 860~960MHz & MIFARE (13.56MHz) - Protocol: ISO/ICE18000-6C EPS Gen 2 | Size: 85.5x54mm - Protocol: ISO/18000-6C +14443A	kom	1.75
	12 14 APA-IC ID ANTENA | 13.56MHz | Anti-magnetic sticker (50mm); Antena (40mm) | R/W - RFID NALEPNICA ZA MOBILNI TELEFON; Opcija štampe za > 200kom	kom	0.95
	12 15 NCF Label Custom P-3M NCF Nalepnica; Ø 30mm; Štampa: obostrano - prema zahtevu, 3M Nalepnica - NCF Lalbels; Ø 30mm; Printing: 2side; One side with 3M Sticker	kom	1.25
	12 21 UHF A7017 UHF RFID PASSIVE LABEL LONG RANGE TAG | Frequency: 860~960MHz - Protocol: ISO/ICE18000-6C EPS Gen 2 | Size: 73.5x21.2mm	kom	1.25

Zadržavamo pravo promene cena, bez obaveze da vas o tome prethodno obavestimo.
Prikazana slika proizvoda, može, ali i ne mora uvek da odgovara originalu.
Naš moto je: Ništa nije konstatno, osim promene! Heraklit 480pne. © 2004. by www.aspekt.rs

ASPEKT System Integration d.o.o.
Požeška br. 67a. Lok. 204, 11030 Beograd, Republika Srbij
Tel. (+ 381 11) 355 7599 Fax. (+ 381 63) 598 033
www.aspekt.rs

CENOVNIK (VP)

25-Sep-25

5780

FOTO	OPIS PROIZVODA / PRODUCT DESCRIPTION	JM	VP CENA (EUR)
	12 22 UHF A7017AT UHF RFID PASSIVE ANTI TAMPER LABEL LONG RANGE TAG | Frequency: 860~960MHz - Protocol: ISO/ICE18000-6C EPS Gen 2 | Size: 73.5x21.2mm	kom	2.45
	12 23 bbb UHF RFID PASSIVE BARCODE LABEL LONG RANGE TAG | Frequency: 860~960MHz - Protocol: ISO/ICE18000-6C EPS Gen 2 | Size: 135x22x12mm	kom	2.45
	12 24 A135-6C UHF RFID METAL ACTIVE LONG RANGE TAG | Frequency: 860~960MHz - Protocol: ISO/ICE18000-6C EPS Gen 2 | Size: 135x22x12mm - Za pričvršćivanje "samorescima" i/ili samolepivom trakom na poleđini	kom	2.95

AUTOMATSKI MOTORNI OTVARAČI / ZATVARAČI KRILNIH VRATA, KAPIJA

	13 1 RAS-140 AUTOMATSKI OTVARAČ / ZATVARAČ KRILNIH VRATA (kapija) | RAS-140 | MAX. 140kg - Za krilo vrata do 1200mm; 24VDC/5A (bez napajanja); -20°C〜60°C; CE Sertifikat - Opening time: 3 ~ 9s / 90°; Holding time: 1 ~ 99s; Dimenzije: 274x85x129mm; 9kg	kom	545.00
	13 2 EAD100-220V AUTOMATSKI OTVARAČ / ZATVARAČ KRILNIH VRATA | EAD100-220V | IP12D; MAX. 280kg - 230V (brushed motor),); -20°C〜60°C; CE Sertifikat - Opening time: 3 ~ 8s / 90°; Holding time: 1 ~ 99s; Dimenzije: 516x105x82mm; 8.5kg	kom	595.00
	13 3 DA180S AUTOMATSKI OTVARAČ / ZATVARAČ KRILNIH VRATA | DA180S| MAX. 180kg Floor Concealed Door Closers - Maximum door weight: 180kg; Maximum door width: 1200mm - Opening and closing time: 6~12S - Power supply: AC220V ±10% 50/60Hz; Rated power: 55W	kom	395.00

BEŽIČNI KOMPLET ZA KRILNA VRATA (KAPIJU) U KOMPLETU

Zadržavamo pravo promene cena, bez obaveze da vas o tome prethodno obavestimo.
Prikazana slika proizvoda, može, ali i ne mora uvek da odgovara originalu.
Naš moto je: Ništa nije konstatno, osim promene! Heraklit 480pne. © 2004. by www.aspekt.rs

ASPEKT System Integration d.o.o.
Požeška br. 67a. Lok. 204, 11030 Beograd, Republika Srbij
Tel. (+ 381 11) 355 7599 Fax. (+ 381 63) 598 033
www.aspekt.rs

CENOVNIK (VP)

25-Sep-25

5780

FOTO			OPIS PROIZVODA / PRODUCT DESCRIPTION	JM	VP CENA (EUR)
	14	1	WSA1 BEŽIČNI KOMPLET | WSA1 | ZA KRILNA VRATA (KAPIJU) U KOMPLETU SA: - RFID BEŽIČNI ČITAČ KARTICA SA TASTATUROM (100 PIN/card users) - 1 x BEŽIČNA ELEKTRO BRAVA ("DROP" BOLT) - 1 x BEŽIČNI EXIT TASTER; 2 x DALJINAC (433MHz Rolling Code technology - Isporučuje se bez baterija	kom	95.00
	14	2	DA5 BEŽIČNI KOMPLET | DA5 | ZA KRILNA VRATA (KAPIJU); IP66 - 433MHz Rolling Code; 4~8 digits PIN, 125KHz EM card	kom	160.00
	14	3	DA4 BEŽIČNI KOMPLET | DA4 | ZA KRILNA VRATA (KAPIJU); IP66 - 433MHz Rolling Code; 4~8 digits PIN, 125KHz EM card	kom	170.00

KONVERTERI USB>WIEGAND; WG>USB; WG>RS485; WG>ETHERNET

	17	1	WGA-USB KONVERTER (WGA-USB) Konekcije WIEGAND NA USB; Sa kablom 0.5m	kom	25.00
	17	2	USB-WGA KONVERTER (USB-WGA) KONEKCIJE USB NA WIEGAND	kom	25.00
	17	3	WGA-RS232 KONVERTER (WGA-RS232) KONEKCIJE WIEGAND NA RS-232	kom	30.00
	17	4	WGA-RS485 KONVERTER (WGA-RS485) KONEKCIJE WIEGAND NA RS-485	kom	35.00

Zadržavamo pravo promene cena, bez obaveze da vas o tome prethodno obavestimo.
Prikazana slika proizvoda, može, ali i ne mora uvek da odgovara originalu.
Naš moto je: Ništa nije konstatno, osim promene! Heraklit 480pne. © 2004. by www.aspekt.rs

ASPEKT System Integration d.o.o.
Požeška br. 67a. Lok. 204, 11030 Beograd, Republika Srbij
Tel. (+ 381 11) 355 7599 Fax. (+ 381 63) 598 033
www.aspekt.rs

CENOVNIK (VP)

25-Sep-25

5780

FOTO			OPIS PROIZVODA / PRODUCT DESCRIPTION	JM	VP CENA (EUR)
	17	5	WGA-TCP	kom	75.00
			KONVERTER (WGA-TCP) KONEKCIJE WIEGAND NA TCP/IP		
	17	7	CA485	kom	30.00
			KONVERTER (CA485) KONEKCIJE RS232 NA RS485		
	17	8	A-Wireless-WG	kom	125.00
			Wireless Wiegand Interface Module; Size:61x36x25mm - Wireless working frequency band:433-473Mhz - Number of supported channels: Use USB cable to set up 50 - Wiegand interface: WG26~WG80 automatic identification, including password button Wireless transmission distance: - Matching 3DB rod antenna line of sight of about 500 meters - External 12DB antenna line of sight of about 1000 meters (optional)		
	17	9	G2	kom	35.00
			Gateway ZA BRAVE & RFID ČITAČE (BLUETOOTH & WIFI) - Obezbeđuje (WiFi) upravljanje BRAVAMA I RFID ČITAČIMA - Izdavanje RFID (mifare) Kartica I ŠIFARA sa PC-a (TTHotel) I "smart" mob. Tel. (TTLock)		

DUPLAIKATOR (ČITAČ / PISAČ) RFID KARTICA

	20	141	AC DUPLIKATOR	kom	55.00
			RFID AC DUPLIKATOR | Material: ABS | Battery: 3V 4pcs AAA | Dimension: 152x80x21mm Frequency LF: 125/250/375/500/625/750/875/1000KHZ | HF: 13.56MHz ISO14443A		

DATA TERMINAL

	21	1	TAFS30	kom	295.00
			DATA TERMINAL (TAFS30) PREPOZNAJE OTISAK PRSTA; RFID KARTICU I ŠIFRU - Kapacitet: 3000 otisaka; 3000 RFID Kartica; Pamti 100,000 Rekorda - Komunikacija: USB, R485, TCP/IP (Opcija WiFi); Režimi rada: 1:N, 1:1 - Brzina identifikacije: ≤1.0s; Napajanje 12VDC, isporučuje se bez napajanja - Dimenzije: 190x80x33mm		

Zadržavamo pravo promene cena, bez obaveze da vas o tome prethodno obavestimo.
Prikazana slika proizvoda, može, ali i ne mora uvek da odgovara originalu.

Naš moto je: Ništa nije konstatno, osim promene! Heraklit 480pne. © 2004. by www.aspekt.rs

ASPEKT System Integration d.o.o.
Požeška br. 67a. Lok. 204, 11030 Beograd, Republika Srbij
Tel. (+ 381 11) 355 7599 Fax. (+ 381 63) 598 033
www.aspekt.rs

CENOVNIK (VP)

25-Sep-25

5780

FOTO			OPIS PROIZVODA / PRODUCT DESCRIPTION	JM	VP CENA (EUR)
	21	2	HASY-F5C	kom	245.00

DATA TERMINAL (HASY-F5C) - skener otiska prsta & rfid čitač kartica (125KHz) & tastatura
- TCP/IP; RS485, USB Memory Disk;
- Software: OS XP/Win2003/Vista/Win7/Win8 (32bit/64bit)
- User:1000; Record Capacity: 100000; Fingerprint Verified Mode: 1:N; 1:1
- FRR: ≤ 1%; FAR: ≤ 0.00001%; Verification Speed: ≤ 1s
- 12VDC / 3 A; Working Temperature: 0-45degree; Dimension: 181*91*36mm
- Interface: Wiegand26/34, Door Lock, Siren, Doorbell, Door
- Release Button (can connect 2 groups)

	21	11	TA301	kom	245.00

DATA TERMINAL (TA301) | PREPOZNAVANJE GEOMETRIJE. LICA | TASTATURA
- Prepoznavanje geo. Lica, i/ili ŠIFRA, i/ili RFID Kartica 125KHz (Opc. 13.56MHz)
- Capacity: Data 160000; Face: 1000 | Password: 1000 | Card : 1000;
- Ambient temperature: -10℃~45℃ | Humidity: 20~80% | Product Size: 172*89*32mm
- Raspoloživ dok traju zalihe

	21	12	DAT03	kom	345.00

DATA TERMINAL (DAT03) | PREPOZNAVANJE GEOMETRIJE. LICA | TASTATURA
- Prepoznavanje geo. Lica, i/ili ŠIFRA, i/ili RFID Kartica (125KHz; Opcija 13.56MHz)
- Capacity: Data 100000; Face: 2000 | Password: 2000 | Card : 2000;
- Ambient temperature: -10℃~45℃ | Humidity: 20~80% | Product Size: 172*89*32mm
- Raspoloživ dok traju zalihe

	21	19	FATZN-002	kom	445.00

DATA TERMINAL (FATZN-002) | Prepoznavanje geometrije lica ("I pod maskom")
- + RFID ČITAČ I MERENJE TEMPERATURE 0^oC ~ 35^oC (≤ ±0.3^oC); ALARM
- CPU: 4Core, 1.8GHz; 2GB Memory, 8GB Storage; 1 RJ45 10M/100M Ethernet port, WIFI

	21	21	STAND-110	kom	75.00

STUBIĆ VISINE 1100mm | MONTAŽA: UREĐAJA ZA PREPOZNAVANJE GEOM. LICA
Stand 1100mm

	21	22	STAND-60	kom	70.00

STUBIĆ VISINE 600mm | MONTAŽA: UREĐAJA ZA PREPOZNAVANJE GEOM. LICA
Stand 600mm

	21	23	STAND-DT	kom	35.00

POSTOLJE DESK TOP | MONTAŽA: UREĐAJA ZA PREPOZNAVANJE GEOM. LICA
Desktop Mounted

Zadržavamo pravo promene cena, bez obaveze da vas o tome prethodno obavestimo.
Prikazana slika proizvoda, može, ali i ne mora uvek da odgovara originalu.
Naš moto je: Ništa nije konstatno, osim promene! Heraklit 480pne. © 2004. by www.aspekt.rs

ASPEKT System Integration d.o.o.
Požeška br. 67a. Lok. 204, 11030 Beograd, Republika Srbij
Tel. (+ 381 11) 355 7599 Fax. (+ 381 63) 598 033
www.aspekt.rs

CENOVNIK (VP)

25-Sep-25

5780

FOTO			OPIS PROIZVODA / PRODUCT DESCRIPTION	JM	VP CENA (EUR)
	21	24	STAND-TM POSTOLJE ZA MONTAŽU NA TROKRAKE ROTACIONE PREPREKE | MONTAŽA: UREĐAJA ZA PREPOZNAVANJE GEOM. LICA Turnstile Mounted	kom	0.00

UPRAVLJANJE I KONTROLA RADA PARTOLNE SLUŽBE

	25	1	GTP-A6200C PATROLA - PRENOSIVI RFID ČITAČ | GTP-A6200C | 125KHz | Vodo-otporan - Detaljna tehnička specifikacija: http://www.aspekt.rs/SRBSecurity.html	kom	140.00
	25	2	GTP-A6200E PATROLA - PRENOSIVI RFID ČITAČ | GTP-A6200E | 125KHz | Vodo-otporan | LED Light - Software (ENG) uključen u cenu; U planu Software (SRB) verzia, uskoro - Detaljna tehnička specifikacija: http://www.aspekt.rs/SRBSecurity.html	kom	195.00
	25	3	GTP-A6200D PATROLA - PRENOSIVI RFID ČITAČ | GTP-A6200D | 125KHz | Vodo-otporan | 1.8" LCD - Detaljna tehnička specifikacija: http://www.aspekt.rs/SRBSecurity.html	kom	145.00
	25	11	GTP-A69002G PATROLA - PRENOSIVI RFID ČITAČ | GTP-A69002G | 125KHz | Vodo-otporan - Detaljna tehnička specifikacija: http://www.aspekt.rs/SRBSecurity.html	kom	345.00
	25	12	GTP-A69002G-GPRS-GPS PATROLA - PRENOSIVI RFID ČITAČ | GTP-A69002G-GPRS-GPS | 125KHz | Vodo-otporan - Detaljna tehnička specifikacija: http://www.aspekt.rs/SRBSecurity.html	kom	395.00
	25	13	GTP-A6900-4G PATROLA - PRENOSIVI RFID ČITAČ | GTP-A6900-4G | 125KHz | Vodo-otporan - Detaljna tehnička specifikacija: http://www.aspekt.rs/SRBSecurity.html	kom	445.00

Zadržavamo pravo promene cena, bez obaveze da vas o tome prethodno obavestimo.
Prikazana slika proizvoda, može, ali i ne mora uvek da odgovara originalu.
Naš moto je: Ništa nije konstatno, osim promene! Heraklit 480pne. © 2004. by www.aspekt.rs

ASPEKT System Integration d.o.o.
Požeška br. 67a. Lok. 204, 11030 Beograd, Republika Srbij
Tel. (+ 381 11) 355 7599 Fax. (+ 381 63) 598 033
www.aspekt.rs

CENOVNIK (VP)

25-Sep-25

5780

FOTO			OPIS PROIZVODA / PRODUCT DESCRIPTION	JM	VP CENA (EUR)
	25	14	GTP-A6900-4G-GPRS-GPS	kom	495.00

PATROLA - PRENOSIVI RFID ČITAČ | GTP-A6900-4G-GPRS-GPS | 125KHz | Vodo-otporan
- Detaljna tehnička specifikacija: http://www.aspekt.rs/SRBSecurity.html

	25	15	GTP-A8000	kom	745.00

PATROLA - PRENOSIVI RFID ČITAČ | GTP-A8000-4G-GPRS | Touch-Screen Guard Tour Probe
- Detaljna tehnička specifikacija: http://www.aspekt.rs/SRBSecurity.html

	25	25	GATP-01C	kom	4.50

RFID ABS ACTIVE TAG - TAG | 125KHz | 70x70x10mm | GATP-01C
- RFID Luminous Checkpoint Tags | Water-resistant, ABS plastic material
- Battery: None, passive tag
- Detaljna tehnička specifikacija: www.aspekt.rs

NAPAJANJA POSEBNE NAMANE ZA KONTROLU PRISTUPA

	27	1	KA70	kom	15.00

NAPAJANJE | POSEBNA NAMENA (KA70); 128x51x36mm
- Input Voltage: AC110-240V; Output Voltage: 12VDC/3A, -20℃~65℃

	27	2	KA80	kom	20.00

NAPAJANJE | POSEBNA NAMENA (KA80), Time Delay: 0-15s; 104 X 69 X 33mm
- Input Voltage: AC110-240V; Output Voltage: 12VDC/3A, -20℃~65℃

	27	5	A208K	kom	25.00

NAPAJANJE | POSEBNA NAMENA (KA70) - BESPREKIDNO NAPAJANJE; 132 x 74 x 39mm
- DC12V; NO, NC; Input Voltage: AC110-240V; Output Voltage: 12VDC/5A, -20℃~65℃

	27	6	A4A-12V8A	kom	35.00

NAPAJANJE | POSEBNA NAMENA (A4A-12V8A), BESPREKIDNO NAPAJANJE; 191*53*40mm
Time Delay: 0-15s; Input Voltage: AC110-240V; Output Voltage: 12VDC/8A, -20℃~65℃

Zadržavamo pravo promene cena, bez obaveze da vas o tome prethodno obavestimo.
Prikazana slika proizvoda, može, ali i ne mora uvek da odgovara originalu.
Naš moto je: Ništa nije konstatno, osim promene! Heraklit 480pne. © 2004. by www.aspekt.rs

ASPEKT System Integration d.o.o.
Požeška br. 67a. Lok. 204, 11030 Beograd, Republika Srbij
Tel. (+ 381 11) 355 7599 Fax. (+ 381 63) 598 033
www.aspekt.rs

CENOVNIK (VP)

25-Sep-25

5780

FOTO		OPIS PROIZVODA / PRODUCT DESCRIPTION		JM	VP CENA (EUR)
EXIT TASTERI					
	28 1	EAB-1405		kom	9.50
		EXIT TASTER (PRITISNI) EAB-1405 (COM/NO)			
	28 2	EAB-1405A		kom	15.00
		EXIT TASTER (PRITISNI) EAB-1405A SA LED PRSTENOM (NO/COM/NC)			
	28 3	EAB-53		kom	0.00
		EXIT TASTER (PRITISNI) EAB-53			
	28 4	EAB-53A		kom	25.00
		EXIT TASTER (PRITISNI) EAB-53A SA LED PRSTENOM			
	28 5	EAB-11E-1		kom	5.00
		EXIT TASTER (PRITISNI) EAB-11E-1 (COM/NO); 91mm x 28mm			
	28 6	EAB-11E-5		kom	0.00
		EXIT TASTER (PRITISNI) EAB-11E-5 SA LED PRSTENOM			
	28 7	SA886		kom	7.00
		EXIT TASTER (PRITISNI) SA886 (COM/NO); 86mm x 86mm			

Zadržavamo pravo promene cena, bez obaveze da vas o tome prethodno obavestimo.
Prikazana slika proizvoda, može, ali i ne mora uvek da odgovara originalu.
Naš moto je: Ništa nije konstatno, osim promene! Heraklit 480pne. © 2004. by www.aspekt.rs

ASPEKT System Integration d.o.o.
Požeška br. 67a. Lok. 204, 11030 Beograd, Republika Srbij
Tel. (+ 381 11) 355 7599 Fax. (+ 381 63) 598 033
www.aspekt.rs

CENOVNIK (VP)

25-Sep-25

5780

FOTO	OPIS PROIZVODA / PRODUCT DESCRIPTION	JM	VP CENA (EUR)
	28 9 E4 EXIT TASTER (PRITISNI) E4 SA LED MARKACIJOM	kom	0.00
	28 10 EAB-11 EXIT TASTER ("NO TOUCH") EAB-11	kom	10.00
	28 11 EAB-10 EXIT TASTER ("NO TOUCH") EAB-10	kom	15.00
	28 12 ACAM-Y803-3A EXIT TASTER ("NO TOUCH") SA UGRAĐENIM NAPAJANJEM (12VDC / 3A) - Door release Switch button and Power Supply , 12V, 3A Power Supply , - NC/NO/COM, AC110V-240VDC, Acrylic Pannel	kom	25.00
	28 13 EAB-401 EXIT TASTER (DODIRNI - "NO TOUCH") EAB-401	kom	0.00
	28 14 EAB-861 EXIT TASTER (DODIRNI - "NO TOUCH") EAB-861	kom	0.00
	28 22 NAT28 EXIT SENZOR "NO TOUCH" Ø28x25mm; 12VDC~24V - UZIDNI TASTER Output contact: NO/NC/COM; with Blue/Green LED lights; Mechanical life: 100,000 tests	kom	15.00

Zadržavamo pravo promene cena, bez obaveze da vas o tome prethodno obavestimo.
Prikazana slika proizvoda, može, ali i ne mora uvek da odgovara originalu.
Naš moto je: Ništa nije konstatno, osim promene! Heraklit 480pne. © 2004. by www.aspekt.rs

ASPEKT System Integration d.o.o.
Požeška br. 67a. Lok. 204, 11030 Beograd, Republika Srbij
Tel. (+ 381 11) 355 7599 Fax. (+ 381 63) 598 033
www.aspekt.rs

CENOVNIK (VP)

25-Sep-25

5780

FOTO	OPIS PROIZVODA / PRODUCT DESCRIPTION	JM	VP CENA (EUR)
	28 23 NAT32 EXIT SENZOR "NO TOUCH" WATERPROOF (IP68); 32x25mm; 12VDC~24V - UZIDNI Output contact: NO/NC/COM; with Blue/Green LED lights; Mechanical life: 100,000 tests	kom	20.00
	28 31 WAS-86 EXIT TASTER | WAS-86 | "NO TOUCH" (BESKONTAKTNI) | 86x86x11.5mm - Input Voltage: DC12-24V; Output Contact: NO NC; Backlight State: Blue to green - Material: Tempered glass; Transmit Distance: 5~8cm; Mechanical Life: 1,000,000 tested - (ENG) Contactless Hand Wave Sensor Switch Button	kom	20.00
	28 32 A4A-505 EXIT TASTER | ASA-505 | "NO TOUCH" (BESKONTAKTNI) | 86x86x11.5mm - Input Voltage: DC12-24V; Output Contact: NO/NC; Backlight State: Blue to Red - Material: Tempered glass; Transmit Distance: 5~8cm; Mechanical Life: 1,000,000 tested - (ENG) Contactless Hand Wave Sensor Switch Button	kom	30.00
	28 33 A4A-505W EXIT TASTER | ASA-505W | "NO TOUCH" (BESKONTAKTNI & BEZ ŽICA) | 86x86x11.5mm - Input Voltage: DC12-24V; Output Contact: NO/NC; Backlight State: Blue to Red - Material: Tempered glass; Transmit Distance: 5~8cm; Mechanical Life: 1,000,000 tested - (ENG) Contactless Hand Wave Sensor Switch Button	kom	50.00
	28 34 OP-24A EXIT TASTER (OPA-24A) | OP-24A | DC9V~DC12V; -30℃~60℃; Relay:NO/NC/OM - Material:Acrylic Panel; APP: Tuya (WiFi); 86x66x23mm	kom	20.00
	28 35 OP-24D EXIT TASTER (OPA-24A) | OP-24D | DC9V~DC12V; -30℃~60℃; Relay:NO/NC/OM - Material:Acrylic Panel; APP: Tuya (WiFi), 86x86x23mm	kom	20.00
	28 53 EBA-20 green Emergency Break Glass Exit Button (green); NO\NC\COM - Dimension: 86x86x50mm;	kom	15.00

OSTALO

Zadržavamo pravo promene cena, bez obaveze da vas o tome prethodno obavestimo.
Prikazana slika proizvoda, može, ali i ne mora uvek da odgovara originalu.
Naš moto je: Ništa nije konstatno, osim promene! Heraklit 480pne. © 2004. by www.aspekt.rs

ASPEKT System Integration d.o.o.
Požeška br. 67a. Lok. 204, 11030 Beograd, Republika Srbij
Tel. (+ 381 11) 355 7599 Fax. (+ 381 63) 598 033
www.aspekt.rs

CENOVNIK (VP)

25-Sep-25

5780

FOTO			OPIS PROIZVODA / PRODUCT DESCRIPTION	JM	VP CENA (EUR)
	29	1	RFID-IC Zasun-150 ZAŠTITNI POKLOPAC (ZASUN) | ABS | ZA RFID ČITAČE; FOTO ĆELIJE ITD. | RFID-IC Zasun-150 - KUĆIŠTE PVC; ZAŠTITNA GUMA: Dimenzije: Out: 150x104x90mm; In: 135x89x84mm	kom	7.00
	29	2	RFID-IC Zasun-245 ZAŠTITNI POKLOPAC (ZASUN) | ABS | ZA RFID ČITAČE; FOTO ĆELIJE ITD. | RFIA-IC Zasun-245 - KUĆIŠTE PVC UV otporno; IP65; ZAŠTITNA GUMA; Sa zaštitnim poklopcem - Dimenzije: Out: 245x143x82mm; In: 230x130x40mm	kom	10.00
	30	84	Extender-A3 PRODUŽETAK ZA AUTOMATSKI OTVARAČ / ZATVARAČ KRILNIH VRATA | A3 - Automatic Door Opener Extender A3 - 31x30mm	kom	15.00
	30	84	Extender-A7 PRODUŽETAK ZA AUTOMATSKI OTVARAČ / ZATVARAČ KRILNIH VRATA | A7 Automatic Door Opener Extender A7 - 80x30mm	kom	20.00

OSTALO ZGODNO ZA UHF I NE SAMO UHF PLATFORMU

	45	81	SPH11/BK NOSAČ ZA UHF ČITAČE | 95~125mm | Nagib -20°; Ugao okretanja +/- 120° - Brend PROST; Nosivst: 5 kg; Boja Crna	kom	10.00

ACC. KOMPLETI (NAJČEŠĆE SE PRIMENJUJU, BILO ZA JEDNA, DVOJA ILI ČETVORA VRATA)

Zadržavamo pravo promene cena, bez obaveze da vas o tome prethodno obavestimo.
Prikazana slika proizvoda, može, ali i ne mora uvek da odgovara originalu.
Naš moto je: Ništa nije konstatno, osim promene! Heraklit 480pne. © 2004. by www.aspekt.rs

ASPEKT System Integration d.o.o.
Požeška br. 67a. Lok. 204, 11030 Beograd, Republika Srbij
Tel. (+ 381 11) 355 7599 Fax. (+ 381 63) 598 033
www.aspekt.rs

CENOVNIK (VP)

25-Sep-25

5780

FOTO	OPIS PROIZVODA / PRODUCT DESCRIPTION	JM	VP CENA (EUR)

47 1 PSKP5780-PV-1V — kom — 445.00

Sistem kontrole pristupa za jedna vrata - KOMPLET 5780 (1V; 2WP), RFID, obuhvata:
ACC. Kontroler | SERIJA 5780 | TCP/IP | za 1 x Vrata| 2 x RFID Čitač| 1 x EXIT Taster
- Q ' ty of users: 20,000 Users; Q ' ty of Event Buffers(offline): 100,000 event buffers
- TCP/IP 10M/100M adaptive, Support APP/4G/Web-server/SDK and Software
2 x RFID Čitač & Tastatura | KAR602Mifare | 13.56MHz | Wg | IP65 |86x86x20mm
- Kućište: "Aluminum alloy"; Tastatura " ne uništiva" | DC 6 ~ 12VDC; Max 6 ~ 12mA
1 x NAPAJANJE | Mean Well | metalno kuciste | 35W | 13.8VDC; 0-2,6A | 2xOut + BATT
- Vin: 85~264 VAC | Vout: 13, 8 VDC (+15% / -5%)
1 x Razvodni orman (ELM): Plastic bostd ABS 400x300x196 TRANSPARENT Door IP65
Priprema Sistema za isporuku | po principu "Kljuc u ruke" (plug & play)
- Izrada radionicke dokumentacije, proizvodnja, sklapanje, instalacija uređaja-opreme
- Instalacija software-a, testiranje sistema ("test report") puštanje u rad
Aplikacija PROTOKOL A-ACC | primarni Web Server | Precizna Evidencija I Kontrola Pristupa
- Dva režima rada: on-line | off-line | Sva podesavanja | on-line monitoring
- Verzije ENG/SRB | Platforma: SQL, ili MSAccess (mdb) | Raspoloživ I SDK

47 2 PSKP5780-PV-2V — kom — 475.00

Sistem kontrole pristupa za dvoja vrata - KOMPLET 5780 (2V; 4WP), obuhvata:
ACC. Kontroler | SERIJA 5780 | TCP/IP | za 2 x Vrata| 4 x RFID Čitač| 2 x EXIT Taster
- Q ' ty of users: 20,000 Users; Q ' ty of Event Buffers(offline): 100,000 event buffers
- TCP/IP 10M/100M adaptive, Support APP/4G/Web-server/SDK and Software
2 x RFID Čitač & Tastatura | KAR602Mifare | 13.56MHz | Wg | IP65 |86x86x20mm
- Kućište: "Aluminum alloy"; Tastatura " ne uništiva" | DC 6 ~ 12VDC; Max 6 ~ 12mA
1 x NAPAJANJE | Mean Well | metalno kuciste | 35W | 13.8VDC; 0-2,6A | 2xOut + BATT
1 x Razvodni orman (ELM): Plastic bostd ABS 400x300x196 TRANSPARENT Door IP65
Priprema Sistema za isporuku | po principu "Kljuc u ruke" (plug & play)
- Izrada radionicke dokumentacije, proizvodnja, sklapanje, instalacija uređaja-opreme
- Instalacija software-a, testiranje sistema ("test report") puštanje u rad
Aplikacija PROTOKOL A-ACC | primarni Web Server | Precizna Evidencija I Kontrola Pristupa
- Dva režima rada: on-line | off-line | Sva podesavanja | on-line monitoring
- Verzije ENG/SRB | Platforma: SQL, ili MSAccess (mdb) | Raspoloživ I SDK

47 3 PSKP5780-PV-4V — kom — 0.00

Sistem kontrole pristupa za dvoja vrata - KOMPLET 5780 (4V; 4WP), obuhvata:
ACC. Kontroler | SERIJA 5780 | TCP/IP | za 4 x Vrata| 4 x RFID Čitač| 4 x EXIT Taster
- Q ' ty of users: 20,000 Users; Q ' ty of Event Buffers(offline): 100,000 event buffers
- TCP/IP 10M/100M adaptive, Support APP/4G/Web-server/SDK and Software
3 x RFID Čitač & Tastatura | KAR602Mifare | 13.56MHz | Wg | IP65 |86x86x20mm
- Kućište: "Aluminum alloy"; Tastatura " ne uništiva" | DC 6 ~ 12VDC; Max 6 ~ 12mA
1 x NAPAJANJE | Mean Well | metalno kuciste | 75W | 13.8VDC; 0-7A | 2xOut + BATT
1 x Razvodni orman (ELM): Plastic bostd ABS 400x300x196 TRANSPARENT Door IP65
Priprema Sistema za isporuku | po principu "Kljuc u ruke" (plug & play)
- Izrada radionicke dokumentacije, proizvodnja, sklapanje, instalacija uređaja-opreme
- Instalacija software-a, testiranje sistema ("test report") puštanje u rad
Aplikacija PROTOKOL A-ACC | primarni Web Server | Precizna Evidencija I Kontrola Pristupa
- Dva režima rada: on-line | off-line | Sva podesavanja | on-line monitoring
- Verzije ENG/SRB | Platforma: SQL, ili MSAccess (mdb) | Raspoloživ I SDK

Zadržavamo pravo promene cena, bez obaveze da vas o tome prethodno obavestimo.
Prikazana slika proizvoda, može, ali i ne mora uvek da odgovara originalu.
Naš moto je: Ništa nije konstatno, osim promene! Heraklit 480pne. © 2004. by www.aspekt.rs

ASPEKT System Integration d.o.o.
Požeška br. 67a. Lok. 204, 11030 Beograd, Republika Srbij
Tel. (+ 381 11) 355 7599 Fax. (+ 381 63) 598 033
www.aspekt.rs

CENOVNIK (VP)

25-Sep-25

5780

FOTO	OPIS PROIZVODA / PRODUCT DESCRIPTION	JM	VP CENA (EUR)

47 3 PSKP5780-PV-2V-T — kom — 575.00

Sistem kontrole pristupa za dvoja vrata (tripod)- KOMPLET 5780 (2V; 4WP), obuhvata:
ACC. Kontroler | SERIJA 5780 | TCP/IP | za 2 x Vrata| 4 x RFID Čitač| 2 x EXIT Taster
- Q ' ty of users: 20,000 Users; Q ' ty of Event Buffers(offline): 100,000 event buffers
- TCP/IP 10M/100M adaptive, Support APP/4G/Web-server/SDK and Software
2 x RFID Čitač & Tastatura | KAR602Mifare | 13.56MHz | Wg | IP65 |86x86x20mm
- Kućište: "Aluminum alloy"; Tastatura " ne uništiva" | DC 6 ~ 12VDC; Max 6 ~ 12mA
1 x NAPAJANJE | Mean Well | metalno kuciste | 35W | 13.8VDC; 0-2,6A | 2xOut + BATT
1 x Razvodni orman (ELM): Plastic bostd ABS 400x300x196 TRANSPARENT Door IP65
Priprema Sistema za isporuku | po principu "Kljuc u ruke" (plug & play)
- Izrada radionicke dokumentacije, proizvodnja, sklapanje, instalacija uređaja-opreme
- Instalacija software-a, testiranje sistema ("test report") puštanje u rad
Aplikacija PROTOKOL A-ACC | primarni Web Server | Precizna Evidencija I Kontrola Pristupa
- Dva režima rada: on-line | off-line | Sva podesavanja | on-line monitoring
- Verzije ENG/SRB | Platforma: SQL, ili MSAccess (mdb) | Raspoloživ I SDK

47 5 PSKP5780-PV-1V-O — kom — 1,450.00

Sistem kontrole pristupa za jedna vrata - KOMPLET 5780 (1V; 2WP), OTISAK, obuhvata:
ACC. Kontroler | SERIJA 5780 | TCP/IP | za 1 x Vrata| 2 x RFID/Otisak Čitač| 1 x EXIT Taster
- 2 x FAR-002 (Otisak & MF1; WG & TCP/IP)), 1 x FAR-S1 (Otisak & MF1; USB)
- Q ' ty of users: 20,000 Users; Q ' ty of Event Buffers (offline): 100,000 event buffers
- TCP/IP 10M/100M adaptive, Support APP/4G/Web-server/SDK and Software
1 x NAPAJANJE | Mean Well | metalno kuciste | 35W | 13.8VDC; 0-2,6A | 2xOut + BATT
- Vin: 85~264 VAC | Vout: 13, 8 VDC (+15% / -5%)
1 x Razvodni orman (ELM): Plastic bostd ABS 400x300x196 TRANSPARENT Door IP65
Priprema Sistema za isporuku | po principu "Kljuc u ruke" (plug & play)
- Izrada radionicke dokumentacije, proizvodnja, sklapanje, instalacija uređaja-opreme
- Instalacija software-a, testiranje sistema ("test report") puštanje u rad
Aplikacija PROTOKOL A-ACC | primarni Web Server | Precizna Evidencija I Kontrola Pristupa
- Dva režima rada: on-line | off-line | Sva podesavanja | on-line monitoring
- Verzije ENG/SRB | Platforma: SQL, ili MSAccess (mdb) | Raspoloživ I SDK

47 7 PSKP5780-PV-3TRIPOD — kom — 1,450.00

Sistem kontrole pristupa za 3 x Pešačka Prepreka - KOMPLET 5780 (3 x 2V; 4WP), obuhvata:
3 x ACC. Kontroler | SERIJA 5780 | TCP/IP | za 2 x Vrata| 4 x RFID Čitač| 2 x EXIT Taster
- Q ' ty of users: 20,000 Users; Q ' ty of Event Buffers(offline): 100,000 event buffers
- TCP/IP 10M/100M adaptive, Support APP/4G/Web-server/SDK and Software
6 x RFID Čitač & Tastatura | KAR602Mifare | 13.56MHz | Wg | IP65 |86x86x20mm
- Kućište: "Aluminum alloy"; Tastatura " ne uništiva" | DC 6 ~ 12VDC; Max 6 ~ 12mA
1 x NAPAJANJE | Mean Well | za DIN šinu | 60W | 13.8VDC; 0-4.3A | 2xOut + BATT
1 x Razvodni orman (ELM): Metalni 500x400x200mm; IP68
Priprema Sistema za isporuku | po principu "Kljuc u ruke" (plug & play)
- Izrada radionicke dokumentacije, proizvodnja, sklapanje, instalacija uređaja-opreme
- Instalacija software-a, testiranje sistema ("test report") puštanje u rad
Aplikacija PROTOKOL A-ACC | primarni Web Server | Precizna Evidencija I Kontrola Pristupa
- Dva režima rada: on-line | off-line | Sva podesavanja | on-line monitoring
- Verzije ENG/SRB | Platforma: SQL, ili MSAccess (mdb) | Raspoloživ I SDK

Zadržavamo pravo promene cena, bez obaveze da vas o tome prethodno obavestimo.
Prikazana slika proizvoda, može, ali i ne mora uvek da odgovara originalu.
Naš moto je: Ništa nije konstatno, osim promene! Heraklit 480pne. © 2004. by www.aspekt.rs

ASPEKT System Integration d.o.o.
Požeška br. 67a. Lok. 204, 11030 Beograd, Republika Srbij
Tel. (+ 381 11) 355 7599 Fax. (+ 381 63) 598 033
www.aspekt.rs

CENOVNIK (VP)

25-Sep-25

5780

FOTO			OPIS PROIZVODA / PRODUCT DESCRIPTION	JM	VP CENA (EUR)
	47	11	RO-K-2V-PLC	kom	1,445.00

Sistem kontrole pristupa za DVOJA vrata - KOMPLET PLC+5780 (2V; 4WP), obuhvata:
ACC. Kontroler | SERIJA 5780 | TCP/IP | ACAB-002; users: 20,000; Buffers(offline): 100,000
- TCP/IP 10M/100M adaptive, Support APP/4G/Web-server/SDK and Software
1 x NAPAJANJE | Mean Well | 12VDC; | 2xOut + BATT; 1 x PLC FBs 24MC
1 x Razvodni orman (ELM): metalni 400x300x20; IP68; osigurač; DIN Utičnica
Priprema Sistema za isporuku | po principu "Kljuc u ruke" (plug & play)
- Izrada radionicke dokumentacije, proizvodnja, sklapanje, instalacija uređaja-opreme
- Instalacija software-a, testiranje sistema ("test report") puštanje u rad
Aplikacija PROTOKOL A-ACC | primarni Web Server | Precizna Evidencija I Kontrola Pristupa
- Dva režima rada: on-line | off-line | Sva podesavanja | on-line monitoring
- Verzije ENG/SRB | Platforma: SQL, ili MSAccess (mdb) | Raspoloživ I SDK

	47	12	RO-K-2V	kom	495.00

Sistem kontrole pristupa za DVOJA vrata - KOMPLET 5780 (2V; 4WP), obuhvata:
ACC. Kontroler | SERIJA 5780 | TCP/IP | ACAB-002; users: 20,000; Buffers(offline): 100,000
- TCP/IP 10M/100M adaptive, Support APP/4G/Web-server/SDK and Software
1 x NAPAJANJE | Mean Well | 12VDC; | 2xOut + BATT
1 x Razvodni orman (ELM): metalni 400x300x20; IP68; osigurač; DIN Utičnica
Priprema Sistema za isporuku | po principu "Kljuc u ruke" (plug & play)
- Izrada radionicke dokumentacije, proizvodnja, sklapanje, instalacija uređaja-opreme
- Instalacija software-a, testiranje sistema ("test report") puštanje u rad
Aplikacija PROTOKOL A-ACC | primarni Web Server | Precizna Evidencija I Kontrola Pristupa
- Dva režima rada: on-line | off-line | Sva podesavanja | on-line monitoring
- Verzije ENG/SRB | Platforma: SQL, ili MSAccess (mdb) | Raspoloživ I SDK

	47	13	K-2V W/O RO	kom	375.00

KOMPLET (5780) 1 x V; 2 x WG Periferija bez RO
1 x Serija GB | RFID Citac Kartica | EM 125KHy | Wiegand 26, 34 | rang: 3 ~ 15cm
- Max. rastojanje od Acc. Kontrol. < 150m | -25°C ~ 70°C | "Water-proof" |LED (red - green)
1 x ACC. KONTROLER | SERIJA 5780 | TCP/IP | 1 x VRATA | 2 x RFID ČITAČ| 1 x EXIT TASTER
- Q ' ty of users: 20,000 Users; Q ' ty of Event Buffers(offline): 100,000 event buffers
- TCP/IP 10M/100M adaptive, Support APP/4G/Web-server/SDK and Softwae
1 x NAPAJANJE | Mean Well | DIN šina | 40W | 13,8VDC; 0-2,9 2 x Out (BATT)
- Vin: 90~264VAC | 40*90*100mm (W*H*D)
1 x ACCU. BATT. LONG | 12VDC / 1.2Ah | T1 | 97 x 43 x 52mm | 0.54 kg
Priprema Sistema za isporuku | po principu "Kljuc u ruke" (plug & play)
- Izrada radionicke dokumentacije, proizvodnja, sklapanje, instalacija uređaja-opreme
- Instalacija software-a, testiranje sistema ("test report") puštanje u rad

	48	1	MACI-109-EM	kom	15.00

USB RFID EM Desk top Čitač kartica (software nije potreban)

Zadržavamo pravo promene cena, bez obaveze da vas o tome prethodno obavestimo.
Prikazana slika proizvoda, može, ali i ne mora uvek da odgovara originalu.
Naš moto je: Ništa nije konstatno, osim promene! Heraklit 480pne. © 2004. by www.aspekt.rs